OFFICE OCCUPANCIES

The B.C. Fire Code requires building owners/occupants to comply with the requirements on this checklist.

These requirements are in addition to those listed in the Fire Safety & You booklet.

Offices uses Include: Low-rise and high-rise office buildings, Professional centres, & Government office buildings.

Checklist: Common Fire Service Requirements

Address: must be visible from road and lane, free from foliage, trees, etc. and in a contrasting colour.	 ☐ Fire lanes: must have an adequate clear width of six unobstructed metres. ☐ Fire Safety Plan: must be reviewed and
☐ Emergency lighting: may be provided by battery packs with remote and attached heads, or by emergency generators that will illuminate specified A/C fixtures or remote light heads. Must be operational, with no visible damage, with heads aimed in proper direction, and serviced and tagged annually by a certified technician.	updated yearly. Fire separations: must have no holes or openings that compromise their purpose. Garbage disposal: commercial containers must be located three meters from combustible build- ings. If inside, commercial containers should have tight-fitting lids and be in fireseparated rooms.
■ Exit doors: must not be blocked from either the inside or outside. Must be unlocked from the inside when the building is occupied. Must have panic hardware that releases when a force of 20 pounds or less is applied.	 'No smoking' signs: must be posted in hazardous areas. Portable fire extinguishers must: be located adjacent to corridors or aisles that provide access to exits. be mounted in a visible location, accessible, and serviced and tagged at least once every 12 months by a certified technician. be full and functioning (no damage, corrosion, leaks, malfunctioning parts or clogged nozzles.) have a minimum rating 2A-10BC. Portable heaters: must be an approved type and kept away from combustibles. Sprinkler valves: must be in the open position, either locked and chained or sealed and monitored electronically. No storage is permitted within 18 inches of the bottom of sprinkler heads
☐ Extension cords: kept to a minimum and not overloaded.	
☐ Fire alarm systems: must have working A/C power-on bulb and be in good working condition with no audible or visual damage. Must have a current service tag (within the last 12 months) and up-to-date logbook.	
☐ Fire doors: must not be blocked or wedged open, including stairwell doors. Must have closures and no wedges used to hold open firerated doors.	
☐ Fire hydrants: must be accessible, free of damage and serviced within the specified date. Private hydrants require annual service, with	



records kept on site.

